

881PM / SAE 100R4

Hydraulic
Suction and Return line



# Part Number									
	inch	mm	Hose O.D. mm	psi	bar	inch	mm	lbs/ft	kg/m
881PM-12PM	3/4	19.0	29.0	305	21	1.6	40	0.32	0.49
881PM-16PM	1	25.4	35.0	250	17	2.2	55	0.42	0.62
881PM-20PM	1-1/4	31.8	42.0	205	14	2.8	70	0.53	0.79
881PM-24PM	1-1/2	38.0	50.0	145	10	3.2	80	0.75	1.12
881PM-32PM	2	50.8	62.0	145	10	3.9	100	0.89	1.33
881PM-40PM	2-1/2	63.5	75.0	145	10	6.7	170	1.21	1.80
881PM-48PM	3	76.2	88.0	145	10	8.9	225	1.45	2.15

Markets



Transportation



Construction



Grounds & Building
Maintenance



Utility
Equipment



Personnel Lift
Equipment



Oil Field Service



Industrial



Automotive

Application:

Recommended for hydraulic
return lines / suction lines.

Construction:

Inner tube : NBR - Synthetic rubber
Reinforcement : Multiple layers of fibre
braids and one helical wire
Outer Cover : CR-Synthetic rubber

Temp. Range

- 40°C to +100°C
(-40°F to +212°F)

Type Approvals: ABS

A

B